



Technical Information

Pro's Pick® Dura-Cube® Water Softening Salt

DESCRIPTION:

Pro's Pick® Dura-Cube® Water Softening Salt is a compacted, cube-shaped, white crystalline sodium chloride which has been manufactured under stringent process control procedures by vacuum evaporation of raw, untreated brine. The salt is obtained from underground deposits by deep well solution mining.

COMPLIANCE:

Pro's Pick® Dura-Cube® Water Softening Salt is acceptable for regeneration of water softener ion exchange resins (P1) by NSF Registration Guideline for Proprietary Substances and Nonfood Compounds (2004). The NSF Nonfood Registration Program is a continuation of the USDA product approval listing, which is based on meeting regulatory requirements for appropriate use, ingredients, and labeling. This product also meets the AWWA Standard for Sodium Chloride B200.

ADDITIVES:

Pro's Pick® Dura-Cube® Water Softening Salt contains no additives.

APPLICATIONS:

Pro's Pick® Dura-Cube® Water Softening Salt is intended for use in regenerating ion-exchange resin in both household and commercial water softeners, and can be utilized effectively in all types of water softening units. Under normal use, the specific size, shape, and density of this product resists mushing, bridging and channeling to provide excellent percolation and brine formation. The product is virtually 100% water soluble. This eliminates messy tank cleaning, providing efficient operation of the water softening unit.

PACKAGING AND STORAGE:

Pro's Pick® Dura-Cube® Water Softening Salt is available only in 50lb. and 80lb. polyethylene bags. To improve caking resistance, the product should be stored in a dry, covered area at humidity below 75%.

METHODS OF ANALYSIS:

Methods of analysis are taken from ASTM E 534-98, AWWA B200-03 and Cargill.

OTHER PROPERTIES:

Pro's Pick® Dura-Cube® Water Softening Salt contains no known allergens, and exhibits virtually no microbiological activity.

CHEMICAL ANALYSIS:

Component	Units	Typical	Specification
Sodium Chloride (dry) ¹	%	99.85	99.80 min.
Calcium & Magnesium (as Ca)	%	0.11	-
Sulfate (as SO ₄)	%	0.04	-
Surface Moisture ²	%	0.02	0.1 max.
Copper (as Cu)	ppm	-	0.5 max.
Iron (as free Fe)	ppm	-	2.0 max.
Heavy Metals (as Pb)	ppm	<1.0	2.0 max.
Water Insolubles	ppm	5	100 max.

¹By difference of impurities.

²110°C for 2 hours.

SIEVE ANALYSIS:

U.S.S. Mesh	Opening Inches	Opening Microns	Typical	Specification
¼	0.250	6350	97	95 min.
Pan	-	-	3	5 max.

Note: Sieve analysis is reported as percent retained.

PRODUCING LOCATION: AKRON, OH
No. 3423 Revised August 2007

CARGILL SALT
P.O. Box 5621
Minneapolis, MN
55440
1-888 385-7258

NOTICE: All of the above statements, recommendations, suggestions and data are based on our laboratory results, and we believe same to be reliable. Nevertheless, with the exception of data showing an express guaranty (such as in the case of products specifically designed for use as nutrient supplements), all such statements, recommendations, suggestions and data hereinabove presented are made without guaranty, warranty or responsibility of any kind on our part.